## AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## LISTING OF CLAIMS:

1. (currently amended) An outlet portion (1) for a nasal rinser, comprising:

an outlet end (2), a connection end (3) and a nozzle shaped channel (4) between the outlet and connection ends,

the nozzle shaped channel (4) having an internal hourglass shape comprising a channel restriction section (5) and an expanded channel outlet section (6), wherein,

the outlet end terminates with the expanded channel outlet section,

the expanded channel outlet section expands toward the outlet end with a maximum interior diameter of the expanded channel outlet section being located at a distal end of the outlet end,

each interior cross-sectional diameter of the nozzle shaped channel is different from all other interior cross-sectional diameters of the nozzle shaped channel,

in use, when a liquid entering the connection end is pressed through the restriction section, a pressure will increase when the liquid passes through the restriction section and a velocity increase when the liquid reaches the expanded channel

Docket No. 1506-1002 Appln. No. 10/069,595

outlet section so that the liquid leaves the outlet end under turbulent flow,

the nozzle shaped channel is housed in an enlarged circumferential portion (12) shaped to seal against edges of an interior of a user's nostril,

an inner diameter of the expanded channel outlet section (6) is greater than an inner diameter of the channel restriction section (5),

the connection end comprises an exterior portion shaped to fit onto a conical tip,

the connection end, the nozzle shaped channel, and the outlet end together define a straight passageway extending through a longitudinal axis from the outlet end to the connection end, and

a largest cross-sectional exterior diameter of the connection end being less than a largest cross-sectional exterior diameter of the enlarged circumferential portion (12).

## 2. (cancelled)

3. (currently amended) An outlet portion according to claim [[2]] 1, wherein an exterior of the enlarged circumference portion (12) is droplet or balloon shaped.

- 4. (previously presented) An outlet portion according to claim 1, wherein the channel (4) is conically shaped at the connection end (3) and has a largest diameter at the connection end (3).
- 5. (previously presented) An outlet portion according to claim 1, which is made of a flexible material.
- 6. (previously presented) A nasal rinser, characterised in that it comprises an outlet portion (1) according to claim 1 and a receptacle for rinsing liquid connected to the outlet portion (1), whereby the receptacle is maneuverable for emptying the rinsing liquid out through the outlet portion (1).
- 7. (original) A nasal rinser according to claim 6, wherein the receptacle is provided with a piston for emptying of the rinsing liquid out through the outlet portion (1).
- 8. (original) A nasal rinser according to claim 6, wherein the receptacle is a flexible, balloon shaped body, which is compressible for emptying of the rinsing liquid out through the outlet portion (1).

9-20. (cancelled)

21. (new) An outlet portion (1) for a nasal rinser, comprising:

a longitudinal axis and a channel extending throughout the longitudinal axis from a channel inlet (3) terminating a first distal end of the channel to a channel outlet (2) terminating a second, opposite distal end of the channel;

an enlarged circumferential portion (12) housing an nozzle shaped channel portion (4) and including the channel outlet (2),

the nozzle shaped channel portion (4) comprising a restriction section (5) connecting to an expanded channel outlet section (6) that expands towards and terminates at the distal end of the channel outlet (2) with the expanded channel outlet section increasing in interior diameter toward the second, distal end of the channel so that a maximum interior diameter of the expanded channel outlet section is located at the second, distalmost end of the channel,

the nozzle shaped channel portion (4) being located in apart of the channel nearer the channel outlet than the channel inlet; and

a connection end (3) connected to the enlarged circumferential portion (12) and including the channel inlet, the connection end comprising an exterior portion shaped to fit onto a conical tip, wherein,

a largest cross-sectional exterior diameter of the connection end is less than a largest cross-sectional exterior diameter of the enlarged circumferential portion (12), and

in use, when a liquid entering the connection end is pressed through the restriction section, a pressure will increase when the liquid passes through the restriction section and a velocity increase when the liquid reaches the expanded channel outlet section so that the liquid leaves the outlet end under turbulent flow.

- 22. (new) The outlet portion of claim 21, wherein the nozzle shaped channel portion is located within an end portion having a flexible, droplet exterior shape.
- 23. (new) The outlet portion of claim 21, wherein the outlet portion is made of a silicone rubber.
- 24. (new) The outlet portion of claim 21, wherein the nozzle shaped channel portion is located within an end portion having a flexible, balloon exterior shape.
- 25. (new) The outlet portion of claim 24, wherein the outlet portion is made of a silicone rubber.

- 26. (new) The outlet portion of claim 1, wherein the enlarged circumferential portion (12) is made of a silicone rubber.
- 27. (new) An outlet portion (1) for a nasal rinser, comprising:

a channel extending from a channel inlet (3) terminating a first distal end of the channel to a channel outlet (2) terminating a second, opposite distal end of the channel;

an enlarged circumferential portion (12) housing a nozzle shaped channel portion (4) and including the channel outlet (2),

the nozzle shaped channel portion (4) comprising a restriction section (5) and a changing interior diameter so that each interior cross-sectional diameter of the restriction section is different from all other interior cross-sectional diameters of the restriction section, the nozzle shaped channel portion (4) being located in apart of the channel nearer the channel outlet than the channel inlet,

the restriction section (5) connecting to an expanded channel outlet section (6) that expands towards and terminates at the distalmost end of the channel outlet (2) with the expanded channel outlet section increasing in interior diameter toward the second, distal end of the channel so that a maximum interior

diameter of the expanded channel outlet section is located at the second, distalmost end of the channel; and

a connection end (3) connected to the enlarged circumferential portion (12) and including the channel inlet, the connection end comprising an exterior portion shaped to fit onto a conical tip, wherein,

a largest cross-sectional exterior diameter of the connection end is less than a largest cross-sectional exterior diameter of the enlarged circumferential portion (12), and

in use, when a liquid entering the connection end is pressed through the restriction section, a pressure will increase when the liquid passes through the restriction section and a velocity increase when the liquid reaches the expanded channel outlet section so that the liquid leaves the outlet end under turbulent flow.

28. (new) The outlet portion of claim 27, wherein the enlarged circumferential portion (12) is made of a silicone rubber.